

View Online at <https://aerobasegroup.com/nsn/4140-01-119-2879>

Speed Adjustments:

Single speed

Length:

8.000 inches

Flow Direction:

Outward

Environmental Protection:

Shock proof

Ambient Temperature At Full Rated Power:

-45.6 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

12000.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

9.1 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

422.000 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac

Prime Mover Power Rating:

1.000 horsepower

Housing Inside Diameter:

6.250 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-a-8625, type 2, class 1 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.