

View Online at <https://aerobasegroup.com/nsn/4140-01-122-7330>

**Speed Adjustments:**

Single speed

**Length:**

1.090 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and vibration proof

**Ambient Temperature At Full Rated Power:**

125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

20500.0

**End Application:**

F-4 aircraft

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

3.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Open

**Mounting Facility Type And Quantity:**

1 ring and 3 clamp

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

55.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

38.0 watts

**Housing Inside Diameter:**

1.990 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Material Specification:**

Qq-a-591 federal specification single material response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0