

View Online at <https://aerobasegroup.com/nsn/4140-01-132-4527>

Speed Adjustments:

Single speed

Length:

Between 1.516 inches and 1.636 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

12200.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.92 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

66.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Housing Inside Diameter:

Between 3.054 inches and 3.074 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Gray enamel finish

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Material Specification:

Qq-a-591 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Fed standard 595 federal standard single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0