

View Online at <https://aerobasegroup.com/nsn/4140-01-132-4527>

**Speed Adjustments:**

Single speed

**Length:**

Between 1.516 inches and 1.636 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

12200.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.92 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

66.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Housing Inside Diameter:**

Between 3.054 inches and 3.074 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Special Features:**

Gray enamel finish

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-591 federal specification single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Fed standard 595 federal standard single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0