

View Online at <https://aerobasegroup.com/nsn/4140-01-133-1512>

Stage Quantity:

1

Speed Adjustments:

Single speed

Length:

8.060 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

66.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3360.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

275.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

256.000 watts

Housing Inside Diameter:

6.250 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Falnge center, plain ends w/7.62 in. Diameter inlet ring; w/o fan performance sensor

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum alloy

Surface Treatment:

Enamel

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.