

View Online at <https://aerobasegroup.com/nsn/4140-01-133-9011>

Speed Adjustments:

Three speed

Length:

32.000 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3600.0

Electrical Connection Type:

Terminal box

Static Pressure At Specificationified Air Flow Rate:

7.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

7000.0 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Housing Inside Diameter:

Between 19.500 inches and 19.531 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Surface Treatment:

Chromate zinc housing and varnish housing

Surface Treatment Specification:

Tt-p-645 federal specification 1st treatment response housing inside and tt-v-119 federal specification 2nd treatment response housing inside

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-f-18953 spec.