

View Online at <https://aerobasegroup.com/nsn/4140-01-133-9011>

**Speed Adjustments:**

Three speed

**Length:**

32.000 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

65.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3600.0

**Electrical Connection Type:**

Terminal box

**Static Pressure At Specificationified Air Flow Rate:**

7.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

7000.0 cubic feet per minute

**Voltage In Volts And Current Type:**

440.0 ac

**Housing Inside Diameter:**

Between 19.500 inches and 19.531 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Material:**

Steel housing

**Surface Treatment:**

Chromate zinc housing and varnish housing

**Surface Treatment Specification:**

Tt-p-645 federal specification 1st treatment response housing inside and tt-v-119 federal specification 2nd treatment response housing inside

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-f-18953 spec.