

View Online at <https://aerobasegroup.com/nsn/4140-01-134-8082>

**Speed Adjustments:**

Single speed

**Width:**

4.690 inches

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Fungus resistant and humidity proof and moisture resistant and salt spray resistant and shock proof and vibration proof

**Operating Speed At Rated Capacity In Rpm:**

2800.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.1 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

85.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

17.000 watts and 39.000 watts

**Housing Inside Diameter:**

4.125 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

60.0 and 400.0

**Height:**

4.690 inches

**Material:**

Aluminum alloy housing

**Unpackaged Unit Weight (non-core):**

1.500 pounds

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-b-23071 spec.