

View Online at <https://aerobasegroup.com/nsn/4140-01-142-2970>

Speed Adjustments:

Single speed

Length:

1.580 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

10900.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

3 clamp

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

30.0 cubic feet per minute

Voltage In Volts And Current Type:

28.0 dc

Prime Mover Power Rating:

0.018 horsepower

Housing Inside Diameter:

1.990 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Special Features:

Inverter driven unit converts dc to ac current

Material:

Aluminum alloy

Material Specification:

Qq-a-591 federal specification single material response

Surface Treatment:

Enamel blade

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response blade

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-c-5541 spec.