

View Online at <https://aerobasegroup.com/nsn/4140-01-143-0706>

Speed Adjustments:

Single speed

Diameter:

8.000 inches

Length:

7.880 inches

Flow Direction:

Outward

Environmental Protection:

Fungus resistant and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3350.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

1000.000 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac

Prime Mover Power Rating:

0.019 horsepower

Housing Inside Diameter:

9.120 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum

Quantity:

1

Surface Treatment:

Anodize

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0