

View Online at <https://aerobasegroup.com/nsn/4140-01-143-4815>

Speed Adjustments:

Single speed

Width:

4.690 inches

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3275.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.2 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

106.0 cubic feet per minute

Voltage In Volts And Current Type:

208.0 ac

Housing Inside Diameter:

4.125 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Height:

4.690 inches

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel housing

Surface Treatment Specification:

Mil-e-5557, type 4 military specification single treatment response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.