

View Online at <https://aerobasegroup.com/nsn/4140-01-144-4581>

Speed Adjustments:

Single speed

Width:

13.047 inches

Length:

6.250 inches

Environmental Protection:

Corrosion resistant and explosion proof and fungus proof and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-46.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3350.0

Outlet Inside Width:

4.000 inches

Outlet Inside Height:

2.500 inches

Static Pressure At Specificationified Air Flow Rate:

1.5 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

8 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Electric noise suppressor and flanged air outlet and radio interference shielding and shock absorber

Air Flow Rate:

450.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

200.0 ac or 230.0 ac

Prime Mover Power Rating:

155.0 watts

Discharge Direction:

Vertical up

Phase:

Three

Frequency In Hertz:

50.0 and 60.0

Height:

6.875 inches

Material:

Aluminum alloy housing

Surface Treatment:

Anodize housing

Style Designator:

Fixed, dual impeller, rectangular outlet

Specification Data:

05869-729424 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0