

View Online at <https://aerobasegroup.com/nsn/4140-01-144-7711>

**Speed Adjustments:**

Two speed

**Length:**

1.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-25.0 degrees celsius and 60.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3150.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Voltage In Volts And Current Type:**

115.0 ac

**Housing Inside Diameter:**

6.375 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0