

View Online at <https://aerobasegroup.com/nsn/4140-01-149-4802>

**Speed Adjustments:**

Single speed

**Length:**

5.000 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5600.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.8 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

130.000 cubic feet per minute

**Voltage In Volts And Current Type:**

208.0 ac

**Prime Mover Power Rating:**

0.080 horsepower

**Housing Inside Diameter:**

Between 3.720 inches and 3.780 inches

**Phase:**

Three

**Special Features:**

Designed for raytheon co program an/trc-170

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Surface Treatment:**

Anodize

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0