

View Online at <https://aerobasegroup.com/nsn/4140-01-149-9936>

**Speed Adjustments:**

Single speed

**Width:**

5.440 inches

**Length:**

3.660 inches

**Environmental Protection:**

Moisture resistant and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

6800.0

**Electrical Connection Type:**

Wire lead

**Outlet Inside Width:**

1.620 inches

**Outlet Inside Height:**

1.500 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 threaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

85.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.067 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Vertical down

**Phase:**

Three

**Height:**

3.880 inches

**Material:**

Steel

**Surface Treatment:**

Zinc blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0