## NSN 4140-01-158-1401

Tubeaxial Fan - Page 1 of 2



Tubeaxiai Fait - Fage Tot 2	Group
View Online at https://aerobasegroup.com/nsn/4140-01-158-1401	
Speed Adjustments:	
Single speed	
Length:	
2.306 inches	
Flow Direction:	
Inward	
Environmental Protection:	
Humidity proof and salt spray proof	
Ambient Tempurature At Full Rated Power:	
-54.0 degrees celsius and 125.0 degrees celsius	
Operating Speed At Rated Capacity In Rpm:	
22500.0	
End Application:	
Military systems	
Electrical Connection Type:	
Connector receptacle	
Static Pressure At Specificationified Air Flow Rate:	
5.5 inches of water	
Drive Type:	
Direct	
Prime Mover Type:	
Electric motor	
Inclosure Type:	
Partially enclosed	
Mounting Facility Type And Quantity:	
4 threaded hole	
Rotation Direction For Which Designed:	
Clockwise	
Air Flow Rate:	
202.0 cubic feet per minute	
Voltage In Volts And Current Type:	
200.0 ac	
Prime Mover Power Rating:	
75.0 watts	
Housing Inside Diameter:	
3.562 inches	
Prime Mover Drive Shaft Bearing Type:	

Ball

**Product Name:** 

Fan, tubeaxial-75 watts

Phase:

Three

## NSN 4140-01-158-1401

Tubeaxial Fan - Page 2 of 2



Frequency In Hertz:	
400.0	
Material:	
Aluminum alloy	
Material Specification:	
II-b-23071 military specification 10th material response	
Surface Treatment:	
Enamel lusterless	
Surface Treatment Specification:	
Ed-std-595 federal standard 5th treatment response	
Style Designator:	
Fixed	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A087a0	
Mil-std (military Standard):	
spec.	