

View Online at <https://aerobasegroup.com/nsn/4140-01-158-1401>

**Speed Adjustments:**

Single speed

**Length:**

2.306 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and salt spray proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

22500.0

**End Application:**

Military systems

**Electrical Connection Type:**

Connector receptacle

**Static Pressure At Specificationified Air Flow Rate:**

5.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

4 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

202.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

75.0 watts

**Housing Inside Diameter:**

3.562 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Product Name:**

Fan, tubeaxial-75 watts

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Material Specification:**

II-b-23071 military specification 10th material response

**Surface Treatment:**

Enamel lusterless

**Surface Treatment Specification:**

Ed-std-595 federal standard 5th treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

spec.