

View Online at <https://aerobasegroup.com/nsn/4140-01-160-7660>

**Speed Adjustments:**

Single speed

**Length:**

1.695 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

-28.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2500.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

27.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.012 horsepower

**Housing Inside Diameter:**

3.000 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Zinc alloy housing

**Surface Treatment:**

Paint housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0