

View Online at <https://aerobasegroup.com/nsn/4140-01-162-2628>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3250.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

Between 190.0 cubic feet per minute and 220.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.043 horsepower

Housing Inside Diameter:

6.375 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

5.92 in. W across flats of venturi

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum alloy

Unpackaged Unit Weight:

2.062 pounds

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0