

View Online at <https://aerobasegroup.com/nsn/4140-01-168-7115>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

4.280 inches

**Length:**

5.000 inches

**Environmental Protection:**

Humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

9500.0

**Electrical Connection Type:**

Connector

**Outlet Inside Width:**

1.410 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 threaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

42.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.174 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular up

**Phase:**

Three

**Height:**

5.360 inches

**Material:**

Steel housing

**Surface Treatment:**

Enamel blade

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0