

View Online at <https://aerobasegroup.com/nsn/4140-01-169-2533>

**Speed Adjustments:**

Single speed

**Length:**

1.580 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof and explosion proof and fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 125.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

20400.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

3 clamp

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

50.0 cubic feet per minute

**Voltage In Volts And Current Type:**

28.0 dc

**Prime Mover Power Rating:**

0.056 horsepower

**Housing Inside Diameter:**

1.990 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Special Features:**

Inverter driven unit converts dc to ac current

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-591 federal specification single material response

**Surface Treatment:**

Enamel blade

**Surface Treatment Specification:**

Mil-e-5557, type 4 military specification single treatment response blade

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-c-5541 spec.