

View Online at <https://aerobasegroup.com/nsn/4140-01-179-0197>

Speed Adjustments:

Single speed

Length:

2.280 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 125.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

10800.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim and 1 ring

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

190.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.092 horsepower

Housing Inside Diameter:

3.562 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Modified casing

Frequency In Hertz:

400.0

Material:

Aluminum alloy

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0