

View Online at <https://aerobasegroup.com/nsn/4140-01-189-4977>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

70.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3250.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim and 4 threaded insert

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

220.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Housing Inside Diameter:

6.375 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

50.0 and 60.0

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel blade

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-c-5541 spec.