

View Online at <https://aerobasegroup.com/nsn/4140-01-190-3278>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Inward

Environmental Protection:

Shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-28.0 degrees celsius and 65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3100.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Err Default:

Err default

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim and 4 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

220.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.032 horsepower

Housing Inside Diameter:

6.375 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Wire lead interface, w/ground connection

Frequency In Hertz:

60.0

Material:

Aluminum alloy

Quantity:

1

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0