NSN 4140-01-198-3822

Tubeaxial Fan - Page 1 of 2

Enamel lusterless housing



View Online at https://aerobasegroup.com/nsn/4140-01-198-3822

Speed Adjustments:
Single speed
Length: 1.500 inches
Flow Direction:
Inward Fraction and Protections
Environmental Protection:
Humidity proof and salt spray resistant and shock proof and vibration proof
Operating Speed At Rated Capacity In Rpm:
3750.0
Electrical Connection Type:
Wire lead
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Rotation Direction For Which Designed:
Counterclockwise
Features Provided:
Safety impeller guard
Air Flow Rate:
130.0 cubic feet per minute
Voltage In Volts And Current Type:
115.0 ac
Prime Mover Power Rating:
0.016 horsepower
Housing Inside Diameter:
4.500 inches
Prime Mover Drive Shaft Bearing Type:
Ball
Phase:
Single
Frequency In Hertz:
400.0
Material:
Plastic polycarbonate blade
Surface Treatment:

NSN 4140-01-198-3822

Tubeaxial Fan - Page 2 of 2



Style Designator:
Fixed
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A087a0