

View Online at <https://aerobasegroup.com/nsn/4140-01-199-9088>

**Speed Adjustments:**

Single speed

**Length:**

1.531 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

22500.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

12.0 cubic feet per minute

**Voltage In Volts And Current Type:**

26.0 ac

**Housing Inside Diameter:**

Between 1.123 inches and 1.125 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Plastic diallyl phthalate blade

**Material Specification:**

Mil-a-8625 military specification single material response housing

**Quantity:**

1

**Surface Treatment:**

Anodize housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.