

View Online at <https://aerobasegroup.com/nsn/4140-01-203-7635>

Speed Adjustments:

Single speed

Width:

5.490 inches

Length:

3.660 inches

Environmental Protection:

Moisture resistant and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

6800.0

Electrical Connection Type:

Connector

Outlet Inside Width:

1.620 inches

Outlet Inside Height:

1.500 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 threaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

85.0 cubic feet per minute

Outlet Location:

Top

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

50.000 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Vertical up

Phase:

Three

Height:

3.880 inches

Material:

Steel

Surface Treatment:

Zinc blade

Style Designator:

Fixed, dual impeller, rectangular outlet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0