

View Online at <https://aerobasegroup.com/nsn/4140-01-207-8124>

Speed Adjustments:

Two speed

Flow Direction:

Outward

Environmental Protection:

Explosion proof

Ambient Temperature At Full Rated Power:

Not rated

Operating Speed At Rated Capacity In Rpm:

1140.0

Electrical Connection Type:

Cord w/attached plug

Err Default:

Err default

Extended Height:

8.000 inches

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 pedestal

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

7460.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac or 230.0 ac

Prime Mover Power Rating:

1.000 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Pedestal mtd; heavy non-tip base; non-oscillating

Frequency In Hertz:

60.0

Height:

5.000 inches

Material:

Aluminum alloy blade

Style Designator:

38a portable adjustable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0