

View Online at <https://aerobasegroup.com/nsn/4140-01-207-8124>

**Speed Adjustments:**

Two speed

**Flow Direction:**

Outward

**Environmental Protection:**

Explosion proof

**Ambient Temperature At Full Rated Power:**

Not rated

**Operating Speed At Rated Capacity In Rpm:**

1140.0

**Electrical Connection Type:**

Cord w/attached plug

**Err Default:**

Err default

**Extended Height:**

8.000 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 pedestal

**Rotation Direction For Which Designed:**

Clockwise and counterclockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

7460.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac or 230.0 ac

**Prime Mover Power Rating:**

1.000 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

Pedestal mtd; heavy non-tip base; non-oscillating

**Frequency In Hertz:**

60.0

**Height:**

5.000 inches

**Material:**

Aluminum alloy blade

**Style Designator:**

38a portable adjustable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0