

View Online at <https://aerobasegroup.com/nsn/4140-01-219-8507>

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

105.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3000.0 and 3100.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 clamp

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

220.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

36.8 watts and 40.3 watts

**Housing Inside Diameter:**

6.375 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Material:**

Plastic blade

**Surface Treatment:**

Enamel housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0