

View Online at <https://aerobasegroup.com/nsn/4140-01-221-9255>

Speed Adjustments:

Single speed

Width:

4.690 inches

Length:

1.500 inches

Flow Direction:

Inward

Environmental Protection:

Humidity proof and fungus proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

25.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

4900.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

182.000 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.060 horsepower

Housing Inside Diameter:

4.125 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Special Features:

Performance sensor

Frequency In Hertz:

50.0 and 60.0

Height:

4.690 inches

Material:

Plastic polycarbonate blade

Surface Treatment:

Enamel housing

Surface Treatment Specification:

Mil-e-5557 military specification single treatment response housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-e-5557 spec.