

View Online at <https://aerobasegroup.com/nsn/4140-01-221-9255>

**Speed Adjustments:**

Single speed

**Width:**

4.690 inches

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Humidity proof and fungus proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

25.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

4900.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

182.000 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

0.060 horsepower

**Housing Inside Diameter:**

4.125 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Special Features:**

Performance sensor

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

4.690 inches

**Material:**

Plastic polycarbonate blade

**Surface Treatment:**

Enamel housing

**Surface Treatment Specification:**

Mil-e-5557 military specification single treatment response housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5557 spec.