

View Online at <https://aerobasegroup.com/nsn/4140-01-223-3896>

**Speed Adjustments:**

Single speed

**Length:**

1.500 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Shock proof

**Ambient Temperature At Full Rated Power:**

105.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2700.0 and 3150.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

195.0 cubic feet per minute and 245.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

34.0 watts and 35.0 watts

**Housing Inside Diameter:**

6.375 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Tt-e-489 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

spec.