

View Online at <https://aerobasegroup.com/nsn/4140-01-224-0331>

**Speed Adjustments:**

Single speed

**Length:**

5.625 inches

**Flow Direction:**

Inward

**Operating Speed At Rated Capacity In Rpm:**

3000.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

136.000 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

0.156 horsepower

**Housing Inside Diameter:**

5.125 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

Mounts in vertical, horizontal or inclined position

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum alloy 356.0

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-a-8625 spec.