

View Online at <https://aerobasegroup.com/nsn/4140-01-225-0974>

Speed Adjustments:

Single speed

Width:

4.690 inches

Length:

1.500 inches

Flow Direction:

Outward

Environmental Protection:

Humidity proof and salt spray resistant and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5300.0

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

175.000 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

0.057 horsepower

Housing Inside Diameter:

4.125 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Height:

4.690 inches

Material:

Plastic polycarbonate blade

Material Specification:

Qq-a-601 federal specification single material response housing

Surface Treatment:

Paint housing

Surface Treatment Specification:

Tt-e-489, type b federal specification single treatment response housing

Style Designator:

45 fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0