

View Online at <https://aerobasegroup.com/nsn/4140-01-238-4361>

**Speed Adjustments:**

Single speed

**Length:**

Between 1.672 inches and 1.796 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Humidity proof

**Ambient Temperature At Full Rated Power:**

-55.0 degrees celsius and 75.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5200.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 rim

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

90.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

23.000 watts

**Housing Inside Diameter:**

Between 3.552 inches and 3.572 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Tt-e-489 federal specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0