

View Online at <https://aerobasegroup.com/nsn/4140-01-239-9919>

**Speed Adjustments:**

Single speed

**Length:**

2.000 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

0.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3300.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

225.0 cubic feet per minute

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

20.000 watts

**Housing Inside Diameter:**

5.920 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Tt-e-489 federal specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0