

View Online at <https://aerobasegroup.com/nsn/4140-01-241-2197>

**Speed Adjustments:**

Single speed

**Length:**

Between 1.470 inches and 1.530 inches

**Flow Direction:**

Inward

**Ambient Temperature At Full Rated Power:**

-10.0 degrees celsius and 55.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3250.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 flange and 8 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

40.0 cubic feet per minute and 33.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

12.0 watts

**Housing Inside Diameter:**

Between 2.805 inches and 2.825 inches

**Prime Mover Drive Shaft Bearing Type:**

Sleeve

**Phase:**

Single

**Special Features:**

3.100 in. Min, 3.160 in. Maximum sq flange ea end venturi tube

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum alloy housing or zinc alloy housing

**Unpackaged Unit Weight:**

1.438 pounds

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0