

View Online at <https://aerobasegroup.com/nsn/4140-01-241-2197>

Speed Adjustments:

Single speed

Length:

Between 1.470 inches and 1.530 inches

Flow Direction:

Inward

Ambient Temperature At Full Rated Power:

-10.0 degrees celsius and 55.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3250.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 8 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

40.0 cubic feet per minute and 33.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

12.0 watts

Housing Inside Diameter:

Between 2.805 inches and 2.825 inches

Prime Mover Drive Shaft Bearing Type:

Sleeve

Phase:

Single

Special Features:

3.100 in. Min, 3.160 in. Maximum sq flange ea end venturi tube

Frequency In Hertz:

50.0 and 60.0

Material:

Aluminum alloy housing or zinc alloy housing

Unpackaged Unit Weight:

1.438 pounds

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0