

View Online at <https://aerobasegroup.com/nsn/4140-01-242-0152>

**Environmental Protection:**

Explosion proof and shock proof and watertight

**Ambient Temperature At Full Rated Power:**

149.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

1200.0

**Electrical Connection Type:**

Terminal block

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Mounting Facility Type And Quantity:**

1 base

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Nonsparking

**Air Flow Rate:**

8000.0 cubic feet per minute

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

400.0 ac

**Prime Mover Power Rating:**

7.500 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Special Features:**

Airfoil designed impellers

**Frequency In Hertz:**

60.0

**Material:**

Steel housing

**Style Designator:**

Fixed, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0