

View Online at <https://aerobasegroup.com/nsn/4140-01-245-2729>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Outward

Environmental Protection:

Dustproof and moisture resistant and salt spray resistant and vibration proof

Ambient Temperature At Full Rated Power:

85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

11000.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange and 3 bolt

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

35.0 cubic feet per minute

Voltage In Volts And Current Type:

26.0 dc

Prime Mover Power Rating:

11.200 watts

Housing Inside Diameter:

2.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Special Features:

Type vax-2-mm

Material:

Aluminum alloy

Material Specification:

Mil-e-5272 military specification single material response

Unpackaged Unit Weight:

0.312 pounds

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0

Mil-std (military Standard):

Mil-e-5272 spec.