

View Online at <https://aerobasegroup.com/nsn/4140-01-245-2729>

**Speed Adjustments:**

Single speed

**Length:**

2.000 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Dustproof and moisture resistant and salt spray resistant and vibration proof

**Ambient Temperature At Full Rated Power:**

85.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11000.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 3 bolt

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

35.0 cubic feet per minute

**Voltage In Volts And Current Type:**

26.0 dc

**Prime Mover Power Rating:**

11.200 watts

**Housing Inside Diameter:**

2.000 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Special Features:**

Type vax-2-mm

**Material:**

Aluminum alloy

**Material Specification:**

Mil-e-5272 military specification single material response

**Unpackaged Unit Weight:**

0.312 pounds

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-e-5272 spec.