

View Online at <https://aerobasegroup.com/nsn/4140-01-246-3090>

**Speed Adjustments:**

Single speed

**Width:**

13.047 inches

**Length:**

6.250 inches

**Environmental Protection:**

Corrosion resistant and explosion proof and fungus proof and humidity proof and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-46.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Outlet Inside Width:**

4.000 inches

**Outlet Inside Height:**

2.500 inches

**Static Pressure At Specificationified Air Flow Rate:**

1.5 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Electric noise suppressor and flanged air outlet and radio interference shielding and shock absorber

**Air Flow Rate:**

450.0 cubic feet per minute

**Outlet Location:**

Bottom

**Voltage In Volts And Current Type:**

200.0 ac or 230.0 ac

**Prime Mover Power Rating:**

155.0 watts

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

6.875 inches

**Material:**

Aluminum alloy housing

**Surface Treatment:**

Anodize housing

**Style Designator:**

Fixed, dual impeller, rectangular outlet

**Specification Data:**

05869-729424 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0