## NSN 4140-01-251-2468



Tubeaxial Fan - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4140-01-251-2468 **Speed Adjustments:** Single speed Length: 1.500 inches Flow Direction: Outward **Environmental Protection:** Fungus resistant and humidity proof and moisture resistant and salt spray resistant and shock proof and vibration proof **Operating Speed At Rated Capacity In Rpm:** 5600.0 **Electrical Connection Type:** Wire lead Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 2 flange and 8 unthreaded hole **Rotation Direction For Which Designed:** Clockwise Air Flow Rate: 73.0 cubic feet per minute **Voltage In Volts And Current Type:** 115.0 ac **Prime Mover Power Rating:** 16.000 watts **Housing Inside Diameter:** 3.000 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase:

Single
Frequency In Hertz:
400.0
Material:
Zinc alloy housing
Style Designator:
Fixed

## NSN 4140-01-251-2468

Tubeaxial Fan - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A087a0