

View Online at <https://aerobasegroup.com/nsn/4140-01-253-8830>

**Speed Adjustments:**

Single speed

**Length:**

1.470 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 71.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

11600.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange and 3 threaded insert

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

32.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

19.500 watts

**Housing Inside Diameter:**

1.890 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize housing and enamel housing

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0