## NSN 4140-01-253-8830

Vaneaxial Fan - Page 1 of 2

Material:

Aluminum alloy



View Online at https://aerobasegroup.com/nsn/4140-01-253-8830 **Speed Adjustments:** Single speed Length: 1.470 inches Flow Direction: Outward **Environmental Protection:** Fungus resistant and humidity proof and salt spray resistant and shock proof and vibration proof **Ambient Tempurature At Full Rated Power:** -54.0 degrees celsius and 71.0 degrees celsius **Operating Speed At Rated Capacity In Rpm:** 11600.0 **Electrical Connection Type:** Wire lead Static Pressure At Specificationified Air Flow Rate: 0.0 inches of water **Drive Type:** Direct **Prime Mover Type:** Electric motor **Inclosure Type:** Fully enclosed **Mounting Facility Type And Quantity:** 1 flange and 3 threaded insert **Rotation Direction For Which Designed:** Counterclockwise Air Flow Rate: 32.0 cubic feet per minute **Voltage In Volts And Current Type:** 115.0 ac **Prime Mover Power Rating:** 19.500 watts **Housing Inside Diameter:** 1.890 inches **Prime Mover Drive Shaft Bearing Type:** Ball Phase: Single Frequency In Hertz: 400.0

## NSN 4140-01-253-8830

Vaneaxial Fan - Page 2 of 2



	Trea	

Anodize housing and enamel housing

**Style Designator:** 

Fixed

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A087a0