

View Online at <https://aerobasegroup.com/nsn/4140-01-263-6435>

**Speed Adjustments:**

Single speed

**Environmental Protection:**

Shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

72.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3035.0

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 base plate

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

240.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

129.000 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

Centrifugal/axial configuration

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0