NSN 4140-01-274-0421

Centrifugal Fan - Page 1 of 2

Speed Adjustments:



View Online at https://aerobasegroup.com/nsn/4140-01-274-0421

Single speed
Width:
19.000 inches
Length:
8.219 inches
Ambient Tempurature At Full Rated Power:
-20.0 degrees fahrenheit and 250.0 degrees fahrenheit
Operating Speed At Rated Capacity In Rpm:
1550.0
Electrical Connection Type:
Cord w/attached plug
Outlet Inside Width:
4.906 inches
Outlet Inside Height:
1.969 inches
Static Pressure At Specificationified Air Flow Rate:
1.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Mounting Facility Type And Quantity:
1 rack
1 rack Rotation Direction For Which Designed:
1 rack
1 rack Rotation Direction For Which Designed:
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location:
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type:
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating:
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating: 95.0 watts
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating: 95.0 watts Prime Mover Drive Shaft Bearing Type:
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating: 95.0 watts Prime Mover Drive Shaft Bearing Type: Ball
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating: 95.0 watts Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction:
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating: 95.0 watts Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction: Vertical up
1 rack Rotation Direction For Which Designed: Clockwise and counterclockwise Air Flow Rate: 300.0 cubic feet per minute Outlet Location: Top Voltage In Volts And Current Type: 110.0 ac Prime Mover Power Rating: 95.0 watts Prime Mover Drive Shaft Bearing Type: Ball Discharge Direction:

NSN 4140-01-274-0421 Centrifugal Fan - Page 2 of 2



Frequency In Hertz:
60.0
Height:
7.000 inches
Material:
Aluminum alloy
Quantity:
1
Style Designator:
Fixed, dual, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A087a0