

View Online at <https://aerobasegroup.com/nsn/4140-01-274-7543>

Length:

3.255 inches

Flow Direction:

Inward

Environmental Protection:

Salt spray resistant and humidity proof and vibration proof and fungus resistant

Ambient Temperature At Full Rated Power:

-55.0 degrees celsius and 85.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

20500.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

8.0 inches of water

Drive Type:

Direct

Mounting Facility Type And Quantity:

3 threaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

35.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

120.0 watts

Housing Inside Diameter:

2.812 inches

Phase:

Three

Special Features:

Additional environmental protection: procedure i, 6 hours with sand and dust velocity at 100 to 500 fpm

Frequency In Hertz:

400.0

Material:

Aluminum

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-862 (asg) , type ii military specification single treatment response

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-a-8625 spec.