

View Online at <https://aerobasegroup.com/nsn/4140-01-293-9315>

Speed Adjustments:

Single speed

Length:

Between 1.508 inches and 1.518 inches

Flow Direction:

Inward

Environmental Protection:

Vibration proof

Operating Speed At Rated Capacity In Rpm:

2350.0 and 2100.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim and 4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

172.0 cubic feet per minute and 149.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

14.0 watts and 18.0 watts

Housing Inside Diameter:

Between 5.900 inches and 5.920 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Capacitor included

Frequency In Hertz:

50.0 and 60.0

Material:

Zinc alloy housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0